


EOLO PU ET ANTIUV



Anti-shock rigid PVC spiral



+80°C

-40°C

AntiUV ether based TPU

COD. **EUEO** - COLOR 26

Color: transparent with black spiral

Features: Special ANTIUV Ether based TPU hose, reinforced with an anti-shock rigid PVC spiral.


Smooth inside, corrugated outside. Light and extremely flexible.

Wall thickness from 0.4 mm to 0,7 mm.

Resistant to UV-rays, abrasion and flexion as well as to microbes and Hydrolysis, this hose features high mechanical properties.

APPLICATIONS:

In agriculture, used on seeders, on agricultural vehicles and equipment.



Technical data

• The technical data shown here were measured at 23°C and 50% humidity
 • **Product on request**, please contact our sales department for info and quantities

CODE	int. ϕ mm	Min wall thick mm	Max wall thick mm	Weight g/m	Vac. mH ₂ O	Bending mm	Coil lgth. m	Vol. m ³
EUE00220000026	22	0,4	2,8	130	2,5	28	20	0,028
EUE00250000026	25	0,4	2,8	150	2,5	30	20	0,034
EUE00300000026	30	0,4	2,8	170	2,5	35	20	0,051
EUE00320000026	31,8	0,4	2,9	190	2	35	20	0,054
EUE00350000026	35	0,5	3,0	210	2	45	20	0,059
EUE00400000026	40	0,5	3,1	260	2	60	20	0,067
EUE00450000026	45	0,5	3,2	300	2	65	20	0,099
EUE00520000026	50,8	0,5	3,4	350	2	70	20	0,111
EUE00600000026	60	0,5	3,8	490	1,6	80	20	0,173
EUE00630000026	63,5	0,5	3,9	540	1,6	80	20	0,183
EUE00700000026	70	0,6	4,2	590	1,6	95	30	0,339
EUE00760000026	76,2	0,6	4,2	640	1,6	100	30	0,365
EUE00800000026	80	0,6	4,5	680	1,6	110	30	0,384
EUE01000000026	100	0,6	4,8	850	1,3	140	30	0,631
EUE01020000026	102	0,6	4,8	870	1,3	140	30	0,643
EUE01200000026	120	0,6	5,4	1190	1	160	30	0,753
EUE01270000026	127	0,6	5,4	1260	1	170	30	0,794
EUE01400000026	140	0,7	5,7	1540	0,9	180	20	0,654
EUE01520000026	152,4	0,7	5,7	1560	0,8	200	20	0,839
EUE01600000026	160	0,7	7,2	2050	0,7	220	20	0,893