

Applicazioni

1. Robotica - Meccatronica
2. Impianti per automazione pneumatica
3. Industria del packaging
4. Industria tessile
5. Automotive
6. Vuoto

Applications

1. Robotique - Mécatronique
2. Installations pour l'automatisation pneumatique
3. Industrie de l'emballage
4. Industrie textile
5. Industrie automobile
6. Vide

Applications

1. Robotics - Mechatronics
2. Systems for pneumatic automation
3. Packaging industry
4. Textile industry
5. Automotive
6. Vacuum


Aplicaciones

1. Robótica - Mecatrónica
2. Instalaciones para automatización neumática
3. Industria de embalaje
4. Industria textil
5. Industria automoción
6. Vacío

Anwendungen

1. Robotik - Mechatronik
2. Systeme für die pneumatische Automatisierung
3. Verpackungsindustrie
4. Textilindustrie
5. Automobil
6. Leer

Materiali	Materials	Werkstoffen	Matériels	Materiales
Corpo: Ottone nichelato CW614N o resina acetica	Body: Nickel plated brass CW614N or acetal resin	Körper: vernickelt Messing CW614N oder acetalharz	Corps: Laiton nickelé CW614N ou résine acétale	Cuerpo: Latón niquelado CW614N o resina acetal
Pulsante: Resina acetica	Sleeve: Acetal resin	Taste: Acetalharz	Bouton: Résine acétale	Pulsador: Resina acetal
Distanziale: Zinco	Spacer ring: Zinc	Distanzring: Zink	Rondelle d'épaisseur: Zinc	Arandela distanciadora: Zinc
Pinza: Acciaio SUS 301	Lock claws: SUS 301 Steel	Bremssattel: Edelstahl SUS 301	Pince: Acier SUS 301	Pinza: Acero SUS 301
Anello raccordo: Resina acetica	Coupling ring: Acetal resin	Mitnehmer-ring: Acetalharz	Bague d'entraînement: Résine acétale	Anillo de conexión: Resina acetal
Guarnizione: NBR esente da silicone	Packing: NBR silicon free	Dichtung: NBR Silikonfrei	Joints: NBS sans silicone	Sello: NBR sin silicona
O-Ring: NBR esente da silicone	O-Ring: NBR silicon free	O-Ringe: NBR Silikonfrei	O-ring: NBS sans silicone	Junta tórica: NBR sin silicona
Attacco girevole: Ottone nichelato CW614N	Rotating body: Nickel plated brass CW614N	Schwenk-verbindung: vernickelt Messing CW614N	Connexion pivotante: Laiton nickelé CW614N	Conexión giratoria: Latón niquelado CW614N



 Pressione e temperatura	 Pressure and Temperature	 Druck und Temperatur	 Pression et Température	 Presión y Temperatura
Tubo: Ø4 – Ø16 mm Pressione (temperatura di utilizzo 20°C): 10 Bar (150 PSI)	Tube: Ø4 – Ø16 mm Pressure (working temperature 20°C): 10 Bar (150 PSI)	Schlauch: Ø4 – Ø16 mm Druck (Betriebstemperatur von 20°C): 10 Bar (150 PSI)	Tuyau: Ø4 - Ø16 mm Pression (température d'utilise de 20°C): 10 bar (150 PSI)	Tubo: Ø4 - Ø16 mm Presión (temperatura de funcionamiento 20 ° C): 10 Bar (150 PSI)
Temperatura: -10°C / +60°C	Temperature: +14°F / +140°F	Temperatur: -10°C / +60°C	Température: -10°C / +60°C	Temperatura: -10°C / +60°C


Tubi consigliati

1)Poliuretano - 2)Poliammide - 3)Polietilene - 4)Nylon


Tuyaux recommandés

1)Polyuréthane 2) Polyamide 3) Polyéthylène 4) Nylon


Recommended tubes

1)Polyurethane - 2)Polyamide - 3)Polyethylene - 4)Nylon


Tubos recomendados

1) Poliuretano - 2) Poliamida - 3) Polietileno - 4) Nylon


Rohrempfehlungen

1)Polyurethan - 2)Polyamid - 3)Polyethylen - 4)Nylon


Fluidi

Aria compressa (altri fluidi a richiesta)


Fluide

Air comprimé (autres fluides sur demande)


Fluid

Compressed air (other fluids on request)


Fluido

Aire comprimido (otros fluidos a petición)


Fluid

Druckluft (andere Medien auf Anfrage)

 Filettatura	 Thread types	 Gewinde	 Filetage	 Roscado
BSPP cilindrica UNI-ISO228 - ISO16030 con O-Ring	BSPP parallel UNI-ISO228 - ISO16030 with O-ring	BSPP zylindrisch UNI-ISO228 - ISO16030 mit O-Ringen	BSPP cylindrique UNI-ISO228 - ISO 16030 avec O-ring	BSPP cilíndrico UNI-ISO 228 - ISO 16030 con junta tórica
BSPT conica UNI-ISO 7 teflonata	BSPT taper UNI-ISO 7 with teflon	BSPT konische UNI-ISO 7 mit Teflon	BSPT conique UNI-ISO7 teflonée	Teflón con recubrimiento BSPT UNI-ISO 7
Metrica ISO/R 262	Metric ISO/R 262	Metrische ISO/R 262	Métrique ISO/R 262	ISO/R 262 métrica


Diametri e filetti

Diametri da 4 mm a 16 mm - Filettature da M5 a 1/2"


Diamètres et filets

Diamètres de 4 mm à 16 mm – Filetages de M5 à 1/2"


Threads and diameters

Diameters from 4 mm to 16 mm - Threads from M5 to 1/2"


Diámetros y roscas

Diámetros de 4 mm a 16 mm - Roscas de M5 a 1/2"


Durchmesser und Gewinde

Durchmesser von 4 mm bis 16 mm - Gewinde von M5 bis 1/2"


Coppia di serraggio


Couple de serrage


Torque specifications



Par de apriete


Angaben Drehmoment

Coppia consigliata Nm	0.8 Nm	M5
Recommended torque Nm	3 Nm	1/8"
Empfohlenes drehmoment Nm	9 Nm	1/4"
Couple de serrage Nm	10 Nm	3/8"
Par aconsejado Nm	12 Nm	1/2"

Misura
Measure
Grösse
Dimensions
Medida

RP 58-B



-  **Adattatore riduzione-maggiorazione**
-  **Reducer-increaser plug-in**
-  **Reduzier Stecker**
-  **Réduction encliquetable**
-  **Reducción**

CODICE/CODE	ØD	ØD1	ØD2	L1	L2	PEZZI/PIECES
RP580604B	4	6	10	16	35	10
RP580804B	4	8	10	13	34	10
RP580806B	6	8	12	15,5	36	10
RP581006B	6	10	12	14	38,5	10
RP581008B	8	10	14	17,5	42	10
RP581208B	8	12	14	17,5	42,5	10
RP581210B	10	12	17	21	46	10