

Material: Brass Nickel Plated
Working Temperature: -20 ÷ 80 C°
Working Temperature: -4 ÷ 176 F°
Working Pressure (max): 20 bar
Working Pressure (max): 290 psi
Vacuum: -99 kPa
Vacuum: 29" Hg
Conformity: Silicone Free

Conformity: RoHS
Conformity:
Conformity:
Conformity:
Application Pneumatic circuits

MA37 Y Fitting



MA37

3D

CODE	TYPE	DTUB0	DTUB02	D2	D2IN	L1	L1IN	L2	L2IN	G	OZ	WTF	WPP	TVH
A0270000	MA37 03 03	3	3	6,8	.267	25	.984	7,5	.295	7,945	.280	-4 ÷ 176	290	29"
A0271010	MA37 04 04	4	4	9	.354	29,5	1.161	9,5	.374	14,3	.504	-4 ÷ 176	290	29"
A0273010	MA37 06 04	6	4	12	.472	34,1	1.343	11	.433	36,1	1.273	-4 ÷ 176	290	29"
A0273030	MA37 06 06	6	6	12	.472	36,5	1.437	12,5	.492	32,7	1.153	-4 ÷ 176	290	29"
A0274030	MA37 08 06	8	6	14	.551	37,5	1.476	14,5	.571	51,1	1.802	-4 ÷ 176	290	29"
A0274040	MA37 08 08	8	8	14	.551	37,5	1.476	14,5	.571	44,1	1.556	-4 ÷ 176	290	29"
A0275040	MA37 10 08	10	8	16	.630	44	1.732	16,5	.650	74,9	2.642	-4 ÷ 176	290	29"
A0275050	MA37 10 10	10	10	16	.630	44,5	1.752	16,5	.650	62,7	2.212	-4 ÷ 176	290	29"
A0276060	MA37 12 12	12	12	19	.748	49	1.929	19,5	.768	95,8	3.379	-4 ÷ 176	290	29"