

HEBELARMATUREN - KAMLOK / CAM & GROOVE COUPLINGS

Vaterteil Typ A nach MIL A-A-59326A mit BSPP Innengewinde (* flachdichtend NBR Gewindedichtung)

Male adapter type A - MIL A-A-59326A with female BSPP thread (*flat sealing with NBR Thread Gasket)

Adapteur type A fileté femelle BSPP - MIL A-A-59326A (*joint plat avec filetage joint NBR)

Camlock tipo A: acople macho - rosca hembra BSPP (*guarnizione piatta con guarnizione del filo NBR)

Męczyzna Typ A - MIL A-A-59326A - Wtyk z gwintem wewnętrznym BSPP (*uszczelnienie gwintu NBR)

Camlock tipo A: versione maschio filettato femmina BSPP (*guarnizione piatta con guarnizione del filo NBR)



*-G with NBR Thread Gasket

NEW

Part-No.	Material	WP	Dimension	Thread	Price
A050AL	Aluminum	10 bar	DN15	1/2"	
A075AL	Aluminum	17 bar	DN20	3/4"	
A100AL	Aluminum	17 bar	DN25	1"	
A100AL-G*	Aluminum	17 bar	DN25	1"	
A125AL	Aluminum	17 bar	DN32	1 1/4"	
A125AL-G*	Aluminum	17 bar	DN32	1 1/4"	
A150AL	Aluminum	17 bar	DN40	1 1/2"	
A150AL-G*	Aluminum	17 bar	DN40	1 1/2"	
A200AL	Aluminum	17 bar	DN50	2"	
A200AL-G*	Aluminum	17 bar	DN50	2"	
A250AL	Aluminum	10 bar	DN65	2 1/2"	
A300AL	Aluminum	8,5 bar	DN80	3"	
A300AL-G*	Aluminum	8,5 bar	DN80	3"	
A400AL	Aluminum	6,5 bar	DN100	4"	
A400AL-G*	Aluminum	6,5 bar	DN100	4"	
A500AL	Aluminum	5 bar	DN125	5"	
A600AL	Aluminum	5 bar	DN150	6"	
A800AL	Aluminum	4 bar	DN200	8"	