

Mutterteil Typ C nach MIL A-A-59326A mit Stutzen für Schelleneinband - NBR Dichtung

Female coupler type C - MIL A-A-59326A with grooved hose-shank - NBR Gasket

Coupleur type C douille annelée sans collerette - MIL A-A-59326A - Joint NBR

Camlock tipo C: acople hembra - espiga para manguera - Junta NBR

Kobieta Typ C - MIL A-A-59326A - Gniazdo z karbowaną końcówką do węża do mocowania opaskami - NBR Uszczelka

Camlock tipo C: versione femmina portagomma - Guarnizione NBR

Part-No.	Material	WP	Dimension	Shank	Price
C050AL	Aluminum	10 bar	DN15	13mm	
C075AL	Aluminum	17 bar	DN20	21mm	
C100AL	Aluminum	17 bar	DN25	27mm	
C125AL	Aluminum	17 bar	DN32	34mm	
C150AL	Aluminum	17 bar	DN40	40mm	
C200AL	Aluminum	17 bar	DN50	51mm	
C250AL	Aluminum	10 bar	DN65	64mm	
C300AL	Aluminum	8,5 bar	DN80	76mm	
C400AL	Aluminum	6,5 bar	DN100	103mm	
C500AL	Aluminum	5 bar	DN125	128mm	
C600AL	Aluminum	5 bar	DN150	152mm	
C800AL	Aluminum	4 bar	DN200	200mm	

