

# HEBELARMATUREN - KAMLOK / CAM & GROOVE COUPLINGS

## Mutterteil Typ C nach MIL A-A-59326A mit Stützen für Schelleneinband - NBR Dichtung

Female coupler type C - MIL A-A-59326A with grooved hose-shank - NBR Gasket

Coupleur type C douille annelée sans collerette - MIL A-A-59326A - Joint NBR

Camlock tipo C: acople hembra - espiga para manguera - Junta NBR

Kobieta Typ C - MIL A-A-59326A - Gniazdo z karbowaną końcówką do węża do mocowania opaskami - NBR Uszczelka

Camlock tipo C: versione femmina portagomma - Guarnizione NBR



| Part-No.   | Material             | WP      | Dimension | Shank | Price |
|------------|----------------------|---------|-----------|-------|-------|
| C050SS2    | SS AISI 316 / 1.4408 | 10 bar  | DN15      | 13mm  |       |
| C075SS     | SS AISI 316 / 1.4408 | 17 bar  | DN20      | 21mm  |       |
| C100SS     | SS AISI 316 / 1.4408 | 17 bar  | DN25      | 27mm  |       |
| C125SS     | SS AISI 316 / 1.4408 | 17 bar  | DN32      | 34mm  |       |
| C150SS     | SS AISI 316 / 1.4408 | 17 bar  | DN40      | 40mm  |       |
| C200SS     | SS AISI 316 / 1.4408 | 17 bar  | DN50      | 51mm  |       |
| C200x150SS | SS AISI 316 / 1.4408 | 17 bar  | DN50      | 40mm  |       |
| C250SS     | SS AISI 316 / 1.4408 | 10 bar  | DN65      | 64mm  |       |
| C300SS     | SS AISI 316 / 1.4408 | 8,5 bar | DN80      | 76mm  |       |
| C400SS     | SS AISI 316 / 1.4408 | 6,5 bar | DN100     | 103mm |       |
| C500SS     | SS AISI 316 / 1.4408 | 5 bar   | DN125     | 128mm |       |
| C600SS     | SS AISI 316 / 1.4408 | 5 bar   | DN150     | 152mm |       |