

Mutterteil Typ C nach MIL A-A-59326A mit Stützen für Schelleneinband - EPDM Dichtung

Female coupler type C - MIL A-A-59326A with grooved hose-shank - EPDM Gasket

Coupleur type C douille annelée sans colerette - MIL A-A-59326A - Joint EPDM

Camlock tipo C: acople hembra - espiga para manguera - Junta EPDM

Kobieta Typ C - MIL A-A-59326A - Gniazdo z karbowaną końcówką do węża do mocowania opaskami - EPDM Uszczelka

Camlock tipo C: versione femmina portagomma - Guarnizione EPDM

Part-No.	Material	WP	Dimension	Shank	Price
C050PP	Polypropylene	8,5 bar	DN20	13mm	
C075PP	Polypropylene	8,5 bar	DN20	21mm	
C100PP	Polypropylene	8,5 bar	DN25	27mm	
C125PP	Polypropylene	6,5 bar	DN32	34mm	
C150x125PP	Polypropylene	6,5 bar	DN40	34mm	
C150PP	Polypropylene	6,5 bar	DN40	40mm	
C200x100PP	Polypropylene	6,5 bar	DN50	27mm	
C200x150PP	Polypropylene	6,5 bar	DN50	40mm	
C200PP	Polypropylene	6,5 bar	DN50	51mm	
C300PP	Polypropylene	5 bar	DN80	76mm	
C400PP	Polypropylene	5 bar	DN100	103mm	

