

HEBELARMATUREN - KAMLOK / CAM & GROOVE COUPLINGS

Mutterteil Typ D nach MIL A-A-59326A mit BSPP Innengewinde - NBR Dichtung (* flachdichtend NBR Gewindedichtung)

Female coupler type D - MIL A-A-59326A with female BSPP thread - NBR Gasket (*flat sealing with NBR Thread Gasket)

Coupleur type D fileté femelle BSPP - MIL A-A-59326A Joint NBR (*joint plat avec filetage joint NBR)

Camlock tipo D: acople hembra - rosca hembra BSPP - Junta NBR (*guarnizione piatta con guarnizione del filo NBR)

Kobieta Typ D - MIL A-A-59326A - Gniazdo z gwintem wewnętrznym BSPP - NBR Uszczelka (*uszczelnienie gwintu NBR)

Camlock tipo D: versione femmina filettato femmina BSPP - Guarnizione NBR (*guarnizione piatta con guarnizione del filo NBR)



*-G with NBR Thread Gasket

NEW

Part-No.	Material	WP	Dimension	Thread	Price
D050AL	Aluminum	10 bar	DN15	1/2"	
D075AL	Aluminum	17 bar	DN20	3/4"	
D100AL	Aluminum	17 bar	DN25	1"	
D100AL-G*	Aluminum	17 bar	DN25	1"	
D125AL	Aluminum	17 bar	DN32	1 1/4"	
D125AL-G*	Aluminum	17 bar	DN32	1 1/4"	
D150AL	Aluminum	17 bar	DN40	1 1/2"	
D150AL-G*	Aluminum	17 bar	DN40	1 1/2"	
D200AL	Aluminum	17 bar	DN50	2"	
D200AL-G*	Aluminum	17 bar	DN50	2"	
D250AL	Aluminum	10 bar	DN65	2 1/2"	
D300AL	Aluminum	8,5 bar	DN80	3"	
D300AL-G*	Aluminum	8,5 bar	DN80	3"	
D400AL	Aluminum	6,5 bar	DN100	4"	
D400AL-G*	Aluminum	6,5 bar	DN100	4"	
D500AL	Aluminum	5 bar	DN125	5"	
D600AL	Aluminum	5 bar	DN150	6"	
D800AL	Aluminum	4 bar	DN200	8"	