

HEBELARMATUREN - KAMLOK / CAM & GROOVE COUPLINGS

Vaterteil Typ F nach MIL A-A-59326A mit BSPT Außengewinde

Male adapter type F - MIL A-A-59326A with male BSPT thread

Adaptateur type F fileté mâle BSPT - MIL A-A-59326A

Camlock tipo F: acople macho - rosca macho BSPT

Męczyzna Typ F - MIL A-A-59326A - Wtyk z gwintem zewnętrznym BSPT

Camlock tipo F: versione maschio filettato maschio BSPT



Part-No.	Material	WP	Dimension	Thread	Price
F050SS	SS AISI 316 / 1.4408	10 bar	DN15	1/2"	
F075SS	SS AISI 316 / 1.4408	17 bar	DN20	3/4"	
F100SS	SS AISI 316 / 1.4408	17 bar	DN25	1"	
F125SS	SS AISI 316 / 1.4408	17 bar	DN32	1 1/4"	
F150SS	SS AISI 316 / 1.4408	17 bar	DN40	1 1/2"	
F200SS	SS AISI 316 / 1.4408	17 bar	DN50	2"	
F250SS	SS AISI 316 / 1.4408	10 bar	DN65	2 1/2"	
F300SS	SS AISI 316 / 1.4408	8,5 bar	DN80	3"	
F400SS	SS AISI 316 / 1.4408	6,5 bar	DN100	4"	
F500SS	SS AISI 316 / 1.4408	5 bar	DN125	5"	
F600SS	SS AISI 316 / 1.4408	5 bar	DN150	6"	