

TEKNOJET 2SN 400

EN 1829-2

RECOMMENDED FOR:
PROFESSIONAL WATER JET CLEANERS

RACCOMANDATO PER:
MACCHINE IDROPULTRICI PROFESSIONALI

Features:



Alternative versions:



other colors available: BLUE, RED, GREY
altri colori disponibili: BLU, ROSSO, GRIGIO

Code	Hose size			Outside diameter		Max working pressure		Min burst pressure		Min bend radius		Weight	
	 D.N. Inch mm			 Inch mm		 PSI Bar		 PSI Bar		 Inch mm		 Lb/ft kg/mt	
TJ2SN04	6	1/4"	6,4	0,57	14,6	5800	400	23200	1600	3,94	100	0,22	0,33
TJ2SN05	8	5/16"	7,9	0,64	16,3	5800	400	23200	1600	4,53	115	0,28	0,41
TJ2SN06	10	3/8"	9,5	0,74	18,7	5800	400	23200	1600	5,12	130	0,34	0,51
TJ2SN08	12	1/2"	12,8	0,86	21,9	5800	400	23200	1600	7,09	180	0,40	0,60


TeknoJET 2SN 3/8"

(9,5mm)

EN 1829-2

 -10°C / +150°C
14°F / +302°F

 400 Bar
40 MPa

5800 Psi

MARKING/MARCATURA: TRANSFER TAPE

OPERATING

TEMPERATURE RANGE:

- 10°C / +135°C
(14°F to +275°F)
with peak of +150°C (302°F)

TEMPERATURA

DI ESERCIZIO:

- 10°C / +135°C
(14°F / +275°F)
con punte di +150°C (302°F)

TUBE:

hot water, detergent and oil synthetic rubber

SOTTOSTRATO:

gomma sintetica resistente a acqua calda, detergenti e oli

REINFORCEMENT:

2 high tensile steel braids

RINFORZO:

2 trecce di acciaio ad alto carico

COVER:

synthetic rubber with extreme abrasion resistance

COPERTURA:

gomma sintetica con estrema resistenza all'abrasione

Note: TO ORDER BLU VERSION PLEASE ADD "B" TO THE CODE
TO ORDER RED VERSION PLEASE ADD "R" TO THE CODE
TO ORDER GREY VERSION PLEASE ADD "G" TO THE CODE
TO ORDER FOREVER VERSION  PLEASE ADD "FV" TO THE CODE