WELORANGE 20 ISO3821 L/L

WELDING HOSE - PROPANE



APPLICATION
Delivery hose, LPG line for welding equipments and industrial applications

TUBE
Black, smooth, **NBR** rubber compound

REINFORCEMENT
High strength synthetic plies

COVER
Orange, smooth, synthetic rubber compound, abrasion and weather resistant

WORKING TEMPERATURE
-13°F +176°F
-25°C +80°C

SPECIFICATIONS
ISO 3821

ID		OD		WEIGHT	WP		BP		COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	m
6	1/4	13	1/2	0.16	20	300	60	900	50/100
8	5/16	15	19/32	0.18	20	300	60	900	50/100
9	23/64	16	5/8	0.20	20	300	60	900	50/100

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING

TGT WELORANGE W.P. 20 BAR ISO3821 ITALY

Tubi Gomma Torino S.p.a. 15040 Mirabello Monferrato (AL) - ITALY - Strada Statale 31 - km 39,4 Nr. 42
Ph: +39 0142.641300 Fax: +39 0142.641350 e-mail: com@tubigommatorino.it

Copyright © TUBI GOMMA TORINO S.p.a. - All rights reserved. The texts and images are owned by Tubi Gomma Torino S.p.A. Even partial reproduction of the catalog is prohibited. In the continuous search for technical and functional improvements, Tubi Gomma Torino S.p.A reserves the right to make changes to its products, which can be made without notice.