

PETROCAR 20 L/L

FUEL AND MINERAL OIL DELIVERY HOSE - LONG LENGTH



APPLICATION

Delivery hose for mineral oils, diesel fuel and gasoline with aromatic contents up to 50%

TUBE

Black, smooth, **NBR** rubber compound

REINFORCEMENT

High strength synthetic plies

COVER

Black, smooth, **NBR/PVC** rubber compound, resistant to oils, fuels, ozone and weather

WORKING TEMPERATURE

-13°F +176°F

-25°C +80°C

										
ID		OD		WEIGHT	WP		BP		BENDING RADIUS	COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	mm	m
5	3/16	13	1/2	0.09	20	300	60	900	40	100
6	1/4	14	9/16	0.15	20	300	60	900	50	100
8	5/16	15	19/32	0.17	20	300	60	900	60	100
8	5/16	17	43/64	0.18	20	300	60	900	65	100
10	3/8	17	43/64	0.20	20	300	60	900	75	100
10	3/8	19	3/4	0.22	20	300	60	900	80	100
13	1/2	21	53/64	0.25	20	300	60	900	95	50
13	1/2	23	29/32	0.27	20	300	60	900	105	50
16	5/8	26	1 5/16	0.35	20	300	60	900	120	50
19	3/4	29	1 9/16	0.40	20	300	60	900	140	50
19	3/4	30	1 3/16	0.42	20	300	60	900	145	50
25	1	36	1 27/64	0.64	20	300	60	900	200	50

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING

TGT PETROCAR W.P. 20 BAR ITALY