ABRACEM /10

CEMENT DELIVERY HOSE



APPLICATION
Delivery hose for concrete, sand, gravel and general abrasive dry materials

TUBE
Black, smooth, **NR**/**SBR** antistatic rubber compound

REINFORCEMENT
High strength synthetic plies

COVER
Black, smooth, antistatic cloth impression **SBR**/**NR**/PVC rubber compound, abrasion and weather resistant

WORKING TEMPERATURE
-40°F +158°F
-40°C +70°C

SPECIFICATIONS
DIN 53516 70 ± 5mm3

ID		OD		WEIGHT	WP		BP		COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	m
51	2	65	2 9/16	1.74	10	150	30	450	40/61
60	2 23/64	74	2 59/64	1.87	10	150	30	450	40/61
70	2 3/4	84	3 5/16	2.18	10	150	30	450	40/61
76	3	86	3 25/64	1.62	10	150	30	450	40/61
76	3	92	3 5/8	2.25	10	150	30	450	40/61
80	3 5/32	90	3 35/64	1.90	10	150	30	450	40/61
80	3 5/32	96	3 25/32	2.60	10	150	30	450	40/61
90	3 35/64	100	3 15/16	2.00	10	150	30	450	40/61
90	3 35/64	106	4 11/64	2.67	10	150	30	450	40/61
102	4	112	4 13/32	2.30	10	150	30	450	40/61
102	4	118	4 41/64	3.18	10	150	30	450	40/61
120	4 23/32	138	5 7/16	4.56	10	150	30	450	40/61

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING



Tubi Gomma Torino S.p.a. 15040 Mirabello Monferrato (AL) - ITALY - Strada Statale 31 - km 39,4 Nr. 42
Ph: +39 0142.641300 Fax: +39 0142.641350 e-mail: com@tubigommatorino.it

Copyright © TUBI GOMMA TORINO S.p.a. - All rights reserved. The texts and images are owned by Tubi Gomma Torino S.p.A. Even partial reproduction of the catalog is prohibited. In the continuous search for technical and functional improvements, Tubi Gomma Torino S.p.A reserves the right to make changes to its products, which can be made without notice.