

Material: Brass Nickel Plated
Working Temperature: -20 ÷ 80 C°
Working Temperature: -4 ÷ 176 F°
Working Pressure (max): 20 bar
Working Pressure (max): 290 psi
Vacuum: -99 kPa
Vacuum: 29" Hg
Conformity: Silicone Free

Conformity: RoHS
Conformity:
Conformity:
Conformity:
Application Pneumatic circuits

MA25 Reducer



MA25

3D

CODE	TYPE	DTUBO	D1	D1IN	D2	D2IN	L1	L1IN	G	OZ	WTF	WPP	TVH
A0150010	MA25 03 04	3	4	.157	6,5	.256	27,5	1.082	2,5	.088	-4 ÷ 176	290	29"
A0151030	MA25 04 06	4	6	.236	9	.354	33,5	1.319	7	.247	-4 ÷ 176	290	29"
A0151040	MA25 04 08	4	8	.315	9	.354	33,5	1.319	10	.353	-4 ÷ 176	290	29"
A0151050	MA25 04 10	4	10	.394	10	.394	31,5	1.240	15	.529	-4 ÷ 176	290	29"
A0151060	MA25 04 12	4	12	.472	12	.472	32,5	1.280	24,5	.864	-4 ÷ 176	290	29"
A0153010	MA25 06 04	6	4	.157	12	.472	35,5	1.398	10	.353	-4 ÷ 176	290	29"
A0153040	MA25 06 08	6	8	.315	12	.472	35	1.378	11,5	.406	-4 ÷ 176	290	29"
A0153050	MA25 06 10	6	10	.394	12	.472	36,5	1.437	16,5	.582	-4 ÷ 176	290	29"
A0153060	MA25 06 12	6	12	.472	12	.472	35,5	1.398	22,2	.783	-4 ÷ 176	290	29"
A0153070	MA25 06 14	6	14	.551	14	.551	37,5	1.476	25	.882	-4 ÷ 176	290	29"
A0154030	MA25 08 06	8	6	.236	14	.551	39,5	1.555	13,5	.476	-4 ÷ 176	290	29"
A0154050	MA25 08 10	8	10	.394	14	.551	37	1.457	15	.529	-4 ÷ 176	290	29"
A0154060	MA25 08 12	8	12	.472	14	.551	39	1.535	23	.811	-4 ÷ 176	290	29"

A0154070	MA25 08 14	8	14	.551	14	.551	38,5	1.516	31,5	1.111	-4 ÷ 176	290	29"
A0155060	MA25 10 12	10	12	.472	16	.630	42	1.654	20	.705	-4 ÷ 176	290	29"
A0155070	MA25 10 14	10	14	.551	16	.630	42	1.654	29,5	1.041	-4 ÷ 176	290	29"
A0156070	MA25 12 14	12	14	.551	19	.748	43	1.693	24	.847	-4 ÷ 176	290	29"
A0157090	MA25 14 16	14	16	.630	22	.866	49,5	1.949	91,8	3.238	-4 ÷ 176	290	29"