


## ADAPTOR SWIVEL FEMALE ORFS- MALE ORFS (1)

RIDUZIONE DIRITTA FEMMINA GIREVOLE ORFS MASCHIO ORFS  
 ADAPTATEUR FEMELLE TOURNANTE ORFS - MÂLE ORFS  
 REDUZIERUNG IG-ORFS / AG - ORFS  
 ADAPTADOR HEMBRA GIRATORIA ORFS - MACHO ORFS

F1 ORFS

F2 ORFS



| Code       | Thread  |       | Dimensions |      |    | Pressure |     |      |
|------------|---------|-------|------------|------|----|----------|-----|------|
|            | F1      | F2    | H          | L1   | L2 | form     | Bar | Psi  |
|            | in      | in    | mm         | mm   | mm |          |     |      |
| AFGO09M006 | 11/16   | 9/16  | 22         | 20   | 10 | X        | 630 | 9136 |
| AFGO11M006 | 13/16   | 9/16  | 24         | 22   | 10 | Y        | 630 | 9136 |
| AFGO13M006 | 1       | 9/16  | 30         | 23   | 10 | Y        | 420 | 6091 |
| AFGO14M006 | 1.3/16  | 9/16  | 36         | 25   | 10 | Y        | 420 | 6091 |
| AFGO15M006 | 1.7/16  | 9/16  | 41         | 26   | 10 | Y        | 420 | 6091 |
| AFGO21M006 | 1.11/16 | 9/16  | 50         | 26.5 | 10 | Y        | 280 | 4060 |
| AFGO32M006 | 2       | 9/16  | 60         | 26.5 | 10 | Y        | 280 | 4060 |
| AFGO11M009 | 13/16   | 11/16 | 24         | 23   | 11 | X        | 630 | 9136 |
| AFGO13M009 | 1       | 11/16 | 30         | 24   | 11 | Y        | 420 | 6091 |
| AFGO14M009 | 1.3/16  | 11/16 | 36         | 26   | 11 | Y        | 420 | 6091 |
| AFGO15M009 | 1.7/16  | 11/16 | 41         | 27   | 11 | Y        | 420 | 6091 |
| AFGO21M009 | 1.11/16 | 11/16 | 50         | 27.5 | 11 | Y        | 280 | 4060 |
| AFGO32M009 | 2       | 11/16 | 60         | 27.5 | 11 | Y        | 280 | 4060 |

**X: Version with crimped nut**

Versione con dado pressato

**Y: Version with slip back nut**


Versione con dado sfilabile

## ADAPTOR SWIVEL FEMALE ORFS- MALE ORFS (2)

RIDUZIONE DIRITTA FEMMINA GIREVOLE ORFS MASCHIO ORFS  
 ADAPTATEUR FEMELLE TOURNANTE ORFS - MÂLE ORFS  
 REDUZIERUNG IG-ORFS / AG - ORFS  
 ADAPTADOR HEMBRA GIRATORIA ORFS - MACHO ORFS

F1 ORFS

F2 ORFS



|   | Code       | Thread  |         | Dimensions |      |      | Pressure |     |      |
|---|------------|---------|---------|------------|------|------|----------|-----|------|
|   |            | F1      | F2      | H          | L1   | L2   | form     | Bar | Psi  |
|   |            | in      | in      | mm         | mm   | mm   |          |     |      |
|   | AFGO13M011 | 1       | 13/16   | 30         | 25.5 | 13   | Y        | 420 | 6091 |
|   | AFGO14M011 | 1.3/16  | 13/16   | 36         | 27.5 | 13   | Y        | 420 | 6091 |
| * | AFGO14M015 | 1.3/16  | 1.7/16  | 36         | 58   | 17.5 | z        | 420 | 6091 |
|   | AFGO15M011 | 1.7/16  | 13/16   | 41         | 29   | 13   | Y        | 420 | 6091 |
| * | AFGO15M021 | 1.7/16  | 1.11/16 | 41         | 60.5 | 17.5 | z        | 420 | 6091 |
|   | AFGO21M011 | 1.11/16 | 13/16   | 50         | 29.5 | 13   | Y        | 280 | 4060 |
|   | AFGO32M011 | 2       | 13/16   | 60         | 29.5 | 13   | Y        | 280 | 4060 |
|   | AFGO14M013 | 1.3/16  | 1       | 36         | 29.5 | 15.5 | X        | 420 | 6091 |
|   | AFGO14M015 | 1.3/16  | 1.7/16  | 41         | 32   | 17.5 | X        | 420 | 6091 |
|   | AFGO15M013 | 1.7/16  | 1       | 41         | 32   | 15.5 | Y        | 420 | 6091 |
|   | AFGO15M021 | 1.7/16  | 1.11/16 | 46         | 33.5 | 17.5 | X        | 420 | 6091 |
|   | AFGO21M013 | 1.11/16 | 1       | 50         | 32   | 15.5 | Y        | 280 | 4060 |
|   | AFGO32M013 | 2       | 1       | 60         | 32   | 15.5 | Y        | 280 | 4060 |
|   | AFGO15M014 | 1.7/16  | 1.3/16  | 41         | 33   | 17   | Y        | 420 | 6091 |
|   | AFGO21M014 | 1.11/16 | 1.3/16  | 50         | 33.5 | 17   | Y        | 280 | 4060 |
|   | AFGO32M014 | 2       | 1.3/16  | 60         | 33.5 | 17   | Y        | 280 | 4060 |
|   | AFGO21M015 | 1.11/16 | 1.7/16  | 50         | 34   | 17.5 | X        | 280 | 4060 |
|   | AFGO32M015 | 2       | 1.7/16  | 60         | 34   | 17.5 | Y        | 280 | 4060 |
|   | AFGO32M021 | 2       | 1.11/16 | 60         | 34   | 17.5 | Y        | 280 | 4060 |

**X: Version with crimped nut**

Versione con dado pressato

**Y: Version with slip back nut**

Versione con dado sfilabile

**Z: Double hexagon version**

Versione con doppio esagono